



**SHERWIN-WILLIAMS.**



# Kennel & Animal Care Facility Guide Specification

---

This Painting Schedule is furnished as a guide to select paint systems, and is not all-inclusive of available Sherwin-Williams products. Specifiers should review the contents and edit to suit the particular project and its location.

The schedule is arranged by substrates, and offers latex, acrylic, water-based epoxy, and waterbased urethane. Each type also includes the available sheens.

Local and National V.O.C. (Volatile Organic Compound) regulations have been taken into consideration. However, because regulations vary by region and frequently change, specifiers should verify that the products comply with local rules. Consult with your Sherwin-Williams representative before finalizing the selection.

If you need additional product information, contact your Sherwin-Williams representative, refer to the Sherwin-Williams Painting Systems Catalog, visit [sherwin-williams.com](http://sherwin-williams.com), or call our Architectural Services Answer Team.

**The Sherwin-Williams Company**  
**Architectural Services Department**  
**800-321-8194 (Telephone)**  
**216-566-1392 (Fax)**  
**[specifications@sherwin.com](mailto:specifications@sherwin.com) (Email)**

**09 91 23 INTERIOR &**

**09 91 13 EXTERIOR**

Issued July 2015

The Sherwin-Williams Company

**Download this document at**  
**[www.swspecs.com](http://www.swspecs.com)**



# Table of Contents

---

## INTERIOR SYSTEMS:

<b>Important Surface Preparation Instructions:</b>	<b>Page 2</b>
<b>Miscellaneous Notes:</b>	<b>Page 2</b>
<b>Interior Topcoats:</b>	<b>Page 3</b>

<b>Offices/Hallways/Common and General Service Areas:</b>	<b>Page 4 – 5</b>
---	-------------------

CMU — Concrete Masonry Units  
Masonry and Concrete — Ceilings and Soffits  
Gypsum Board — Walls  
Gypsum Board — Ceilings and Soffits  
Wood — Painted Doors, Frames, Trim, or Chair Rails  
Wood — Stained Trim or Chair Rails  
Ferrous Metal — Doors, Frames, and Miscellaneous Metals  
Ferrous Metal — High Performance Finish (Including Handrails)  
Non-Ferrous Metal — Galvanized/Aluminum  
Non-Ferrous Metal — High Performance Finish (Including Handrails)

<b>Employee Food Service Area/Restrooms:</b>	<b>Pages 6 – 7</b>
--	--------------------

CMU — Concrete Masonry Units  
Masonry and Concrete — Ceilings and Soffits  
Gypsum Board — Walls  
Gypsum Board — Ceilings and Soffits  
Ferrous Metal — Doors, Frames, and Miscellaneous Metals  
Ferrous Metal — High Performance Finish (Including Handrails)  
Non-Ferrous Metal — Galvanized/Aluminum  
Non-Ferrous Metal — High Performance Finish (Including Handrails)

<b>Animal Holding Areas, Vivarium and Cage Wash Areas, including Ceilings:</b>	<b>Page 8</b>
--	---------------

CMU — Concrete Masonry Units  
Cement Board — Walls & Ceilings  
Ferrous Metal — Doors, Frames, Handrails, and Miscellaneous Metals  
Non-Ferrous Metal — Doors, Frames, Handrails, and Miscellaneous Metals

<b>Exposed Ceilings and Decking:</b>	<b>Page 9</b>
--------------------------------------	---------------

Ferrous Metal Decking — including Bar Joists  
Non-Ferrous Decking

<b>Concrete Floors:</b>	<b>Page 10</b>
-------------------------	----------------

## EXTERIOR SYSTEMS:

<b>Exterior Topcoats:</b>	<b>Page 11</b>
<b>Concrete and Masonry — Smooth:</b>	<b>Page 12</b>
<b>CMU and Block Areas — Porous:</b>	<b>Page 13</b>
<b>Ferrous Metals:</b>	<b>Page 14</b>
<b>Non-Ferrous Metals:</b>	<b>Page 14</b>
<b>Wood:</b>	<b>Page 15</b>
<b>Plaster/Stucco:</b>	<b>Page 16</b>

## Important Surface Preparation Instructions:

---

*Verify the existence of lead based paints on the project. Buildings constructed after 1978 are less likely to contain lead based paints. If lead based paints are suspected on the project, all removal must be done in accordance with the EPA Renovation, Repair and Painting rule and all applicable state and local regulations. State and local regulations may be more strict than those set under the federal regulations. Verify that Owner has completed a Hazardous Material Assessment Report for the project prior to issuing of Drawings.*

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority. Removal must be done in accordance with EPA Renovation, Repair and Painting Rule and all related state and local regulations. Care should be taken to follow all state and local regulations which may be more strict than those set under the federal RRP Rule.

## Miscellaneous Notes:

---

### **SURFACE PREPARATION:**

- A. Proper product selection, surface preparation, and application affect coating performance. Coating integrity and service life will be reduced because of improperly prepared surfaces. Selection and implementation of proper surface preparation ensures coating adhesion to the substrate and prolongs the service life of the coating system.
- B. Selection of the proper method of surface preparation depends on the substrate, the environment, and the expected service life of the coating system. Economics, surface contamination, and the effect on the substrate will also influence the selection of surface preparation methods.
- C. The surface must be dry and in sound condition. Remove oil, dust, dirt, loose rust, peeling paint or other contamination to ensure good adhesion.
- D. Remove mildew before painting by washing with a product designed for mildew removal from the affected surface. Clean and rinse according to manufacturer's written instructions.
- E. Previously Coated Surfaces: maintenance painting will frequently not permit or require complete removal of all old coatings prior to repainting. However, all surface contamination such as oil, grease, loose paint, mill scale, dirt, foreign matter, rust, mold, mildew, mortar, efflorescence, and sealers must be removed to assure sound bonding to the tightly adhering old paint. Glossy surfaces of old paint films must be clean and dull before repainting. Thorough washing with an abrasive cleanser will clean and dull in one operation, or, wash thoroughly and dull by sanding. Spot prime any bare areas with an appropriate primer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system. Check for compatibility by applying a test patch of the recommended coating system, covering at least 2 to 3 square feet. Allow to dry one week before testing adhesion per ASTM D3359. If the coating system is incompatible, complete removal is required per ASTM D4259
- F. No exterior painting should be done immediately after a rain, during foggy weather, when rain is predicted, or when the temperature is below 50°F, unless products are designed specifically for these conditions. On large expanses of metal siding, the air, surface and material temperatures must be 50°F or higher to use low temperature products.
- G. This schedule is not inclusive of all Sherwin-Williams products; other products and finishes are available.
- H. Not all products are VOC compliant nationwide; visit related websites for CARB, OTC, SCAQMD for current VOC regulations.  
CARB — <http://www.arb.ca.gov/coatings/coatingsrules.htm>  
OTC — [www.otcair.org](http://www.otcair.org)  
SCAQMD — <http://www.aqmd.gov/rules>

# Kennel & Animal Care Interior Paint Schedule

---

## Miscellaneous Notes (Cont):

---

- I. Product names, logos, brands and other trademarks are the property of their respective trademark holders.
- J. Refer to the current MSDS/EDS for specific VOCs (calculated per 40 CFR 59.406). VOCs may vary by base and sheen.
- K. Coating Maintenance Manual: upon conclusion of the project, the Contractor or paint manufacture/supplier shall furnish a coating maintenance manual, such as Sherwin-Williams "Custodian Project Color and Product Information" report or equal. Manual shall include an Area Summary with finish schedule, Area Detail designating where each product/color/finish was used, product data pages, Material Safety Data Sheets, care and cleaning instructions, touch-up procedures, and color samples of each color and finish used.

## Specifier Notes (Interior Topcoats):

---

- a. **ProMar<sup>®</sup> 200 Zero VOC Interior Latex** — A durable, professional quality zero VOC vinyl acrylic topcoat available in Flat, Low Sheen, Eg-Shel and Semi-Gloss finishes.
- b. **Harmony<sup>®</sup> Interior Latex** — A durable zero VOC interior paint. Harmony also contains an anti-microbial agent that inhibits the growth of mold and mildew on the paint film — which also inhibits the growth of bacterial odors. Its Odor Eliminating Technology reduces common odors to help keep rooms smelling fresher, longer.
- c. **Pro Industrial<sup>™</sup> Pre-Catalyzed Water Based Epoxy** — A single-component, water based acrylic epoxy that offers the durability and resistance to stains and most cleaning solvents usually characteristic of two-component water based epoxies. Available in Eg-Shel and Semi-Gloss finishes.
- d. **Pro Industrial<sup>™</sup> Water Based Catalyzed Epoxy** — A two-component waterborne epoxy formulated to provide excellent corrosion resistance, chemical resistance, abrasion resistance and moisture resistance. Available in Eg-Shel and Gloss finishes.
- e. **Pro Industrial<sup>™</sup> Acrylic Coating** — A single-component, light industrial, 100% acrylic coating that flows and levels to a smooth finish. Available in Eg-Shel, Semi-Gloss and Gloss finishes.
- f. **Waterbased Acrolon<sup>™</sup> 100 Urethane** — A two-component water based high performance polyurethane with exceptional solvent and chemical resistance.
- g. **Macropoxy 646-100 Fast Cure Epoxy** — A two-component solvent based and high solids semi-gloss polyamide epoxy for concrete and steel in higher performance environments.
- h. **Pro Industrial<sup>™</sup> Waterborne Acrylic Dryfall** — A dryfall for use on exposed ceilings and overhead surfaces in commercial, warehouse and manufacturing facilities. Available in Flat, Eg-Shel and Semi-Gloss finishes.
- i. **HydroGloss Waterbased Urethane** — A single component, high performance, acrylic/polyester waterbased urethane. It provides toughness, flexibility, abrasion resistance and excellent UV resistance.
- j. **Minwax<sup>®</sup> Waterbased Polyurethane Varnish** — A durable, clear finish that combines polyurethane protection with the convenience of a waterbased finish.

## Recommended Finishes:

<b>Ceilings and Soffits:</b>	Flat, Eg-Shel or Semi-Gloss Finish
<b>Walls:</b>	Eg-Shel or Semi-Gloss Finish (unless otherwise noted)
<b>Trim:</b>	Semi-Gloss or Gloss Finish

## Offices/Hallways/Common and General Service Areas:

---

### CMU — Concrete Masonry Units

Gloss — **High Performance Finish**

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

Semi-Gloss Finish

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [ProMar® 200 Zero VOC Latex Semi-Gloss](#), B31W2600 Series

Alternate Finish

**2 coats:** [Harmony® Interior Latex Semi-Gloss](#), B10 Series

Eg-Shel Finish

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B26-2600 Series

Alternate Finish

**2 coats:** [Harmony® Interior Latex Eg-Shel](#), B9 Series

Eg-Shel — **High Performance Finish**

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series

### Masonry and Concrete — Ceilings and Soffits

Eg-Shel Finish

**1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300

**2 coats:** [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series

Alternate Finish

**2 coats:** [Harmony® Interior Latex Eg-Shel](#), B9 Series

### Gypsum Board — Walls

Gloss — **High Performance Finish**

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

Semi-Gloss Finish

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [ProMar® 200 Zero VOC Latex Semi-Gloss](#), B31W2600 Series

Alternate Finish

**2 coats:** [Harmony® Interior Latex Semi-Gloss](#), B10 Series

Eg-Shel Finish

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series

Alternate Finish

**2 coats:** [Harmony® Interior Latex Eg-Shel](#), B9 Series

Eg-Shel — **High Performance Finish**

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series

## Offices/Hallways/Common and General Service Areas (Cont.):

---

### Gypsum Board — Ceilings and Soffits

Eg-Shel Finish

- 1 coat: [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
- 2 coats: [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series

Alternate Finish

- 2 coats: [Harmony® Interior Latex Eg-Shel](#), B9 Series

### Wood — Painted Doors, Frames, Trim, or Chair Rails

Semi-Gloss Finish

- 1 coat: [PrepRite® ProBlock® Latex Primer/Sealer](#), B51 Series
  - 2 coats: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
- Alternate Finish
- 2 coats: [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Semi-Gloss](#), K46 Series

### Wood — Stained Trim or Chair Rails

Stained Finish

- Stain: [Minwax® 250 Stain](#)
- 2 coats: [Minwax® Waterbased Polyurethane Varnish, Satin or Gloss](#) (Sand lightly between coats)

### Ferrous Metal — Doors, Frames, and Miscellaneous Metals

Semi-Gloss Finish

- 1 coat: [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
  - 2 coats: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
- Alternate Finish
- 2 coats: [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Semi-Gloss](#), K46 Series

### Ferrous Metal — High Performance Finish (Including Handrails)

Eg-Shel or Gloss Finish

- 1 coat: [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
- 2 coats: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

### Non-Ferrous Metal — Galvanized/Aluminum

Semi-Gloss Finish

- 1 coat: [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
  - 2 coats: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
- Alternate Finish
- 2 coats: [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Semi-Gloss](#), K46 Series

### Non-Ferrous Metal — High Performance Finish (Including Handrails)

Eg-Shel or Gloss Finish

- 1 coat: [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
- 2 coats: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

## Employee Food Service Areas/Restrooms:

---

### CMU — Concrete Masonry Units

#### Gloss — High Performance Finish

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

#### Semi-Gloss Finish

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Semi-Gloss](#), K46 Series

#### Eg-Shel Finish

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Eg-Shel](#), K45 Series

#### Eg-Shel — High Performance Finish

**Filler:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series

### Masonry and Concrete – Ceilings and Soffits

#### Eg-shel Finish

**1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300

**2 coats:** [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series

#### Alternate Finish

**2 coats:** [Harmony® Interior Latex Eg-Shel](#), B9 Series

### Gypsum Board — Walls

#### Gloss — High Performance Finish

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

#### Semi-Gloss Finish

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Semi-Gloss](#), K46 Series

#### Eg-Shel Finish

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Eg-Shel](#), K45 Series

#### Eg-Shel — High Performance Finish

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series

### Gypsum Board — Ceilings and Soffits

#### Eg-Shel Finish

**1 coat:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600

**2 coats:** [ProMar® 200 Zero VOC Interior Latex Flat](#), B30-2600 Series

#### Alternate Finish

**2 coats:** [Harmony® Interior Latex Eg-Shel](#), B9 Series



## Employee Food Service Area/Restrooms (Cont.):

---

### **Ferrous Metal — Doors, Frames, and Miscellaneous Metals**

Semi-Gloss Finish

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate Finish

**2 coats:** [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Semi-Gloss](#), K46 Series

### **Ferrous Metal — High Performance Finish (Including Handrails)**

Eg-Shel or Gloss Finish

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [HydroGloss Single Component Waterbased Urethane Gloss](#), B65 Series

Alternate Finish

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

### **Non-Ferrous Metal — Galvanized/Aluminum**

Semi-Gloss Finish

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate Finish

**2 coats:** [Pro Industrial™ Pre-Catalyzed Water Based Epoxy Semi-Gloss](#), K46 Series

### **Non-Ferrous Metal — High Performance Finish (Including Handrails)**

Eg-Shel or Gloss Finish

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [HydroGloss Single Component Waterbased Urethane Gloss](#), B65 Series

Alternate Finish

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

## Animal Holding Areas, Vivarium and Cage Wash Areas:

---

### CMU — Concrete Masonry Units

Semi-Gloss — **High Performance Solvent Based Epoxy Finish** (frequently washed and sanitized areas)

**Filler:** [Kem Cati-Coat® HS Epoxy Filler/Sealer](#), B42-400 Series (number of coats as required to fill voids, pinholes and to provide a proper dense basecoat — confirm with mock up and before application of finish coats)

**Finishes:** (2) Two Coats of [Macropoxy® 646-100 Fast Cure Epoxy](#), B58-620 (solvent based epoxy)

### Cement Board — Walls & Ceilings (frequently washed and sanitized areas)

Semi-Gloss — **High Performance Finish**

**Primer:** Not Required

**Finishes:** (2) Two Coats of [Macropoxy® 646-100 Fast Cure Epoxy](#), B58- 620 (solvent based epoxy)

Note: I) All service requirements (use of sanitizing agents, washing/disinfecting procedures and all other conditions) must be fully qualified and confirmed before specifying any of the above systems. A General Polymers wall system may have to be considered after a review of the service requirements. Other waterbased (Pro Industrial) epoxy options may be appropriate too.

II) Solvent based epoxy finishes may darken or discolor after application and full cure.

### Ferrous Metal — Doors, Frames, Handrails, and Miscellaneous Metals

Gloss — **High Performance Finish**

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

Alternate Finish

**2 coats:** [Waterbased Acrolon™ 100 Polyurethane Gloss](#), B65-720 Series

Eg-Shel — **High Performance Finish**

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series

### Non-Ferrous Metal — Doors, Frames, Handrails, and Miscellaneous Metals

Gloss — **High Performance Finish**

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

Alternate Finish

**2 coats:** [Waterbased Acrolon™ 100 Polyurethane Gloss](#), B65-720 Series

Eg-Shel — **High Performance Finish**

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series

## Exposed Ceilings and Decking (Larger overhead areas, if applicable):

---

### **Ferrous Decking — including Bar Joists**

Eg-Shel or Semi-Gloss Finish

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Waterborne Acrylic Dryfall, Eg-Shel or Semi-Gloss](#), B42-80 Series

### **Non-Ferrous Decking**

Eg-Shel or Semi-Gloss Finish

**1 coat:** [Pro Industrial™ Waterborne Acrylic Dryfall, Eg-Shel, or Semi-Gloss](#), B42-80 Series

**2 coats:** [Pro Industrial™ Waterborne Acrylic Dryfall, Eg-Shel, or Semi-Gloss](#), B42-80 Series

## Concrete Floors — Coating Systems:

---

### Light Duty (Foot Traffic)

**2 coats:** [ArmorSeal® Tread-Plex® WB Acrylic Floor Coating](#), B90-100 Series

### Medium Duty

**2 coats:** [ArmorSeal® 8100 Finish](#) B70-8100 Series

**Heavy Duty** (Includes, but not limited to, animal holding areas, vivarium, cage wash, restroom and locker room floors):

Decorative (quartz) Color System: General Polymers Ceramic Carpet 554 Decorative Broadcast System (see data pages)

- 3579
- 3554
- 5900F
- 3554
- 5900F
- 3745 (Grout and Seal Coat)

Decorative (mosaic broadcast) Color System: General Polymers Bio Flake Decorative Flooring System (see data pages)

- 3477
- 4080/5080
- 3745
- 6750/6755
- 3745
- 4685

Decorative epoxy terrazzo system (for general service areas, facility corridors, etc.):

General Polymers Thin Set Epoxy Terrazzo # 1100 System (see data pages)

- 3556
- 3579/3520/5270
- 3579/3520/5270
- 3520
- 4401

Solid Color System for wash down/holding areas as noted above: General Polymers Trafficote 105 Self Leveling Slurry (see data pages).

- 3579
- 3561/5350/5310 (1/16" smooth)
- 3561/5350/5310 & 5310 (1/8" non skid)
- 3561
- 3745

Solid Color System for employee kitchen and food preparation areas: General Polymers 12S Urethane Slurry Systems (see data pages):

- 4060/4060/5055
- 3477
- 4080/5080
- 5310 and 4090T/5095 as optional topcoat

Sherwin-Williams offers a full line of patching materials, basecoats, seamless floor coatings, polished concrete and other high performance floor finishes. Please contact your local Sherwin-Williams representative for detailed information and specifications.

# Kennel & Animal Care Exterior Paint Schedule

---

## Specifier Notes — Topcoats:

---

- a. **A-100® Exterior Latex** — A 100% acrylic formula that offers a durable, professional quality coating available in Flat, Satin, Low-Sheen and Gloss finishes.
  
- b. **Loxon XP™ Masonry Coating** — A high build exterior masonry coating that can be applied to fresh concrete and masonry surfaces. It is highly alkali and efflorescent resistant. This may be applied to a surface with a pH of 6 to 13.
  
- c. **ConFlex XL™ Elastomeric High Build Coating**— An elastomeric coating that provides excellent flexibility, durability, and weather resistance.  
This product will protect against wind-driven rain when used on tilt-up, precast, or poured-in-place concrete, CMU, and stucco. Available in smooth or textured finishes.
  
- d. **Waterbased Acrolon™ 100 Urethane** — A two-component, waterbased, acrylic urethane enamel. It is designed for high performance protection with outstanding exterior gloss and color retention properties.
  
- e. **Pro Industrial™ Acrylic Coating** — A single-component, light industrial, 100% acrylic coating that flows and levels to a smooth finish. Available in Eg-Shel, Semi-Gloss, and Gloss finishes.
  
- f. **UltraCrete Textured Masonry Topcoat** — A 100% acrylic aggregate filled coating used to produce a textured finish on exterior surfaces.

## Recommended Finishes:

---

- Body:** Flat or Satin (unless otherwise noted)  
**Trim:** Semi-Gloss or Gloss Finish (unless otherwise noted)

# Kennel & Animal Care Exterior Paint Schedule

---

## Concrete and Masonry — Smooth:

---

### Gloss Finish

**1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300

**2 coats:** [A-100® Exterior Latex Gloss](#), A8 Series

### Satin Finish

**1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300

**2 coats:** [A-100® Exterior Latex Satin](#), A82 Series

### Low Sheen Finish

**1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300

**2 coats:** [A-100® Exterior Latex Low Sheen](#), A12 Series

### Flat Finish

**1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300

**2 coats:** [A-100® Exterior Latex Flat](#), A6 Series

### Flat Finish — **High Build Coating**

**2 coats:** [Loxon XP™ Masonry Coating](#), A24-1400 Series

## CMU and Block Areas — Porous:

---

### Gloss Finish

**1 coat:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [A-100® Exterior Latex Gloss](#), A8 Series

### Satin Finish

**1 coat:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [A-100® Exterior Latex Satin](#), A82 Series

### Low Sheen Finish

**1 coat:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [A-100® Exterior Latex Low Sheen](#), A12 Series

### Flat Finish

**1 coat:** [Loxon® Block Surfacer](#), A24W200

**2 coats:** [A-100® Exterior Latex Flat](#), A6 Series

### Flat Finish — **High Build Coating**

**2 coats:** [Loxon XP™ Masonry Coating](#), A24-1400 Series

## Ferrous Metals and Non-Ferrous Metals (except stainless steel):

---

### High Performance Finish

Gloss Finish

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Waterbased Acrolon™ 100 Polyurethane Gloss](#), B65-720 Series

Semi-Gloss Finish

**1 coat:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

**2 coats:** [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series



## Wood:

---

### Gloss Finish

**1 coat:** [Exterior Latex Wood Primer](#), B42W8041

**2 coats:** [A-100<sup>®</sup> Exterior Latex Gloss](#), A8 Series

### Satin Finish

**1 coat:** [Exterior Latex Wood Primer](#), B42W8041

**2 coats:** [A-100<sup>®</sup> Exterior Latex Satin](#), A82 Series

### Low Sheen Finish

**1 coat:** [Exterior Latex Wood Primer](#), B42W8041

**2 coats:** [A-100<sup>®</sup> Exterior Latex Low Sheen](#), A12 Series

## Plaster/Stucco:

---

### Gloss Finish

- 1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
- 2 coats:** [A-100® Exterior Latex Gloss](#), A8 Series

### Satin Finish

- 1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
- 2 coats:** [A-100® Exterior Latex Satin](#), A82 Series

### Low Sheen Finish

- 1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
- 2 coats:** [A-100® Exterior Latex Low Sheen](#), A12 Series

### Flat Finish

- 1 coat:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
- 2 coats:** [A-100® Exterior Latex Flat](#), A6 Series

### Flat Finish — **High Build Coating**

- 2 coats:** [Loxon XP™ Masonry Coating](#), A24-1400 Series





©2015 The Sherwin-Williams Company