

LOXON XP® MASONRY COATING

WATERPROOFING PROTECTION IN ONE LESS COAT.



ULTIMATE PROTECTION FOR MASONRY.

Loxon XP[®] provides exceptional protection against wind-driven rain, alkali and efflorescence. This direct-to-concrete and masonry high-build coating offers maximum performance in one less coat compared to conventional coatings



and there is no need for priming. The jobs go fast and the great look lasts a long time. Protect concrete from damp conditions and weathering, plus meet the most stringent VOC regulations.

LOXON XP KEY BENEFITS	
• Exceptional flexibility, durability and fade resistance.	Meets the most stringent VOC regulations.
 Protects against wind-driven rain, alkali, cracking and efflorescence. 	 Low temperature application down to 35°F.
 High build for one less coat compared to conventional masonry coatings. 	 Suitable for all types of vertical concrete and masonry surfaces including tilt-up, precast, poured-in-place, CMU, cement block and stucco. Available in a wide range of colors.
 Save time and turn job fast — applies directly to bare concrete with a pH as high as 13. Can be applied to fresh concrete and masonry less than 28 days old. No primer needed. 	• For best results this product should be applied at a minimum of 14–18 mils wft (wet film thickness) and 6.4–8.3 dft (dry film thickness).
 Delivers excellent directional rolling and sheen for a uniform finish. 	

LOXON XP IS BROUGHT TO YOU BY A NAME YOU KNOW AND TRUST.

For more than 145 years, Sherwin-Williams has provided contractors, builders, property managers, architects and designers with the trusted products they need to build their business and satisfy customers. Loxon XP is just one more way we bring you industry-leading coating technology — innovation you can pass on to your customers.

Plus with more than 3,500 stores and 1,800 sales representatives across North America, personal service and expert advice is always available near jobsites. Find out more about Loxon XP at your nearest Sherwin-Williams store or to have a sales representative contact you, call **800-524-5979**.

