

PRODUCT GUIDE — ELASTOMERIC

A flexible film designed for use on masonry and concrete that prevents water penetration and hides hairline cracks, making uniform, pinhole-free jobs easier and faster to achieve.



	CONFLEX™ SHERLASTIC® ELASTOMERIC COATING CF16 SERIES	CONFLEX XL™ TEXTURED HIGH BUILD ACRYLIC COATING CF12-800 SERIES	CONFLEX XL™ HIGH BUILD ACRYLIC COATING CF11 SERIES
CHARACTERISTICS	<ul style="list-style-type: none"> Acrylic elastomeric for exterior vertical surfaces Finish 0-10 units @ 85° <50 g/L VOC Application temperature 50°-100°F 	<ul style="list-style-type: none"> Acrylic elastomeric for exterior vertical surfaces Finish 0-10 units @ 85° <100 g/L VOC Application temperature 50°-100°F 	<ul style="list-style-type: none"> Acrylic elastomeric for exterior vertical surfaces Finish 0-10 units @ 85° <50 g/L VOC Application temperature 50°-100°F
TEXTURE	Smooth	Fine, Medium, Coarse Texture	Smooth
COLORS	Many	Most	Most
TINTABLE	Yes	Yes	Yes
COVERAGE	115-160 sq. ft. (two-coat system), 60-80 sq. ft. (one-coat system)	70-80 sq. ft. (per coat)	100-125 sq. ft. (two-coat system), 50-60 sq. ft. (one-coat system)
DRY TIME (TO RECOAT)	24 hours	24 hours	24 hours
SUBSTRATES	CMU, Concrete, Concrete/ Cinder Block, Stucco, Split Face Block	CMU, Concrete, Concrete/ Cinder Block, Stucco, Tilt-Up (poured in place), Split Face Block	CMU, Brick, Concrete, Stucco, Tilt-Up (poured in place)
PRODUCT PROPERTIES	5, 8, 9, 10, 11, 12, 13	5, 8, 9, 11, 12, 13	5, 8, 9, 10, 11, 12, 13

PRODUCT PROPERTY KEY

- | | | |
|----------------------------------|------------------------------|---------------------|
| 1 Alkali Resistant | 6 Self-Priming | 11 Flexibility |
| 2 Efflorescence Resistant | 7 Block Filling | 12 Elongation |
| 3 Binds/Restores Chalky Surfaces | 8 Wind-Driven Rain Resistant | 13 Tensile Strength |
| 4 Water Repellant | 9 Water Vapor Permeability | |
| 5 Mildew Resistant | 10 Hairline Crack Bridging | |

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams representative for additional technical data and instructions.