

## PRODUCT GUIDE — PRIMERS & SEALERS

Sherwin-Williams primers and sealers are formulated to solve typical coating problems while helping to make the finish coat smooth and uniform, so you get a great-looking finish and long-lasting results.



	CONFLEX™ BLOCK FILLER CF01W0050	LOXON® WATER BLOCKING PRIMER/ FINISH LX12W0050	LOXON® CONCRETE & MASONRY PRIMER/ SEALER LX02W0050	LOXON® ACRYLIC BLOCK SURFACER LX01W0200
CHARACTERISTICS	<ul style="list-style-type: none"> <li>Acrylic block filler for interior/exterior</li> <li>Finish 0-5 units @ 85°</li> <li>&lt;50 g/L VOC</li> <li>Application temperature &gt;50°F</li> </ul>	<ul style="list-style-type: none"> <li>Acrylic polymer primer/finish for interior/exterior</li> <li>Finish Flat, 0-10 units @ 85°</li> <li>&lt;50 g/L VOC</li> <li>Application temperature &gt;40°F</li> </ul>	<ul style="list-style-type: none"> <li>Acrylic primer/sealer for interior/exterior</li> <li>Finish 0-10 units @ 85°</li> <li>&lt;50 g/L VOC</li> <li>Application temperature &gt;50°F</li> </ul>	<ul style="list-style-type: none"> <li>Acrylic block filler for interior/exterior</li> <li>Flat Finish</li> <li>&lt;100 g/L VOC</li> <li>Application temperature &gt;35°F</li> <li>Lightweight</li> <li>Accepts high performance finishes</li> </ul>
TEXTURE	Smooth	Smooth	Smooth	Smooth
COLORS	Off White	White	White	Off White
TINTABLE	No	Yes	Yes	Yes
COVERAGE	75-100 sq. ft.	75-125 sq. ft.	200-300 sq. ft.	50-100 sq. ft.
DRY TIME (TO RECOAT)	18 hours (Latex), 48 hours (Alkyd)	2-4 hours	24 hours	<b>Latex:</b> 24 hours (@ 35°-55°F), 8 hours (@ 55°F+) <b>Alkyd &amp; High Performance:</b> 48 hours (@ 35°-55°F+)
SUBSTRATES	CMU, Concrete, Concrete/Cinder Block, Masonry Surfaces	CMU, Concrete, Concrete/Cinder Block, Masonry Surfaces, Stucco, Tilt-Up (poured in place)	Brick, Concrete, Concrete/Cinder Block, Fiber Cement Siding, Masonry Surfaces, Stucco, Plaster, Cement Siding	CMU, Concrete, Concrete/Cinder Block, Masonry Surfaces, Stucco
PRODUCT PROPERTIES	7	1, 2, 5, 6, 7	1, 2, 6	1, 2, 6, 7

### PRODUCT PROPERTY KEY

- |                                  |                              |                     |
|----------------------------------|------------------------------|---------------------|
| 1 Alkali Resistant               | 6 Self-Priming               | 11 Flexibility      |
| 2 Efflorescence Resistant        | 7 Block Filling              | 12 Elongation       |
| 3 Binds/Restores Chalky Surfaces | 8 Wind-Driven Rain Resistant | 13 Tensile Strength |
| 4 Water Repellant                | 9 Water Vapor Permeability   |                     |
| 5 Mildew Resistant               | 10 Hairline Crack Bridging   |                     |

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams Representative for additional technical data and instructions.



LOXON® ACRYLIC CONDITIONER LX03 SERIES	LOXON® VERTICAL CONCRETE STAIN LX31-50 SERIES	LOXON® VERTICAL SEMI-TRANSPARENT CONCRETE STAIN LX31T0075	LOXON® WATER REPELLANT 40% SILANE LX31T0040	LOXON® WATER REPELLANT 40% SILANE LOWER VOC LX31T0840	CONFLEX™ WATER REPELLANT 7% SILOXANE CF31T0007
<ul style="list-style-type: none"> <li>Acrylic sealer for interior/exterior</li> <li>&lt;50 g/L VOC</li> <li>Application temperature &gt;50°F</li> </ul>	<ul style="list-style-type: none"> <li>Acrylic stain for exterior vertical surfaces</li> <li>Finish 0-8 units @ 60°</li> <li>&lt;50 g/L VOC</li> <li>Application temperature 50°-90°F</li> </ul>	<ul style="list-style-type: none"> <li>Acrylic stain for exterior vertical surfaces</li> <li>Finish 0-4 units @ 60°</li> <li>&lt;50 g/L VOC</li> <li>Application temperature 50°-90°F</li> </ul>	<ul style="list-style-type: none"> <li>Silane water repellant for exterior vertical and horizontal surfaces</li> <li>494 g/L VOC</li> <li>Application temperature 32°-90°F</li> </ul>	<ul style="list-style-type: none"> <li>Silane water repellant for exterior vertical and horizontal surfaces</li> <li>343 g/L VOC</li> <li>Application temperature 50°-90°F</li> </ul>	<ul style="list-style-type: none"> <li>Silane water repellant for exterior vertical and horizontal surfaces</li> <li>&lt;50 g/L VOC</li> <li>Application temperature 50°-90°F</li> </ul>
Smooth	Smooth	Smooth	Smooth	Smooth	Smooth
Guide-Coat White & Clear	Many	Many	Clear	Clear	Clear
Yes	Yes	Yes	No	No	No
200-300 sq. ft.	50-250 sq. ft.	150-400 sq. ft.	25-200 sq. ft.	25-200 sq. ft.	25-200 sq. ft.
3 hours	15 minutes	2 hours	3 hours Note: If a second coat is required to uniform the application, this product MUST be applied wet-on-wet.	3 hours Note: If a second coat is required to uniform the application, this product MUST be applied wet-on-wet.	3 hours Note: If a second coat is required to uniform the application, this product MUST be applied wet-on-wet.
Brick, Concrete, Concrete/Cinder Block, Stucco, Cement Siding	Concrete, Masonry Surfaces, Stucco, Tilt-Up (poured in place), Split Face Block, Cement Siding	Concrete, Masonry Surfaces, Stucco, Tilt-Up (poured in place), Split Face Block	Brick, Concrete, Concrete/Cinder Block, Masonry Surfaces, Stucco, Tilt-Up (poured in place), Split Face Block	Brick, Concrete, Concrete/Cinder Block, Masonry Surfaces, Stucco, Tilt-Up (poured in place), Split Face Block	Brick, Concrete, Concrete/Cinder Block, Masonry Surfaces, Stucco, Tilt-Up (poured in place), Split Face Block
1, 2, 3, 6	1, 2, 4, 5, 6	1, 2, 4, 5, 6	1, 2, 4, 6	1, 2, 4, 6	1, 2, 4, 6

**PRODUCT PROPERTY KEY**

- |                                  |                              |                     |
|----------------------------------|------------------------------|---------------------|
| 1 Alkali Resistant               | 6 Self-Priming               | 11 Flexibility      |
| 2 Efflorescence Resistant        | 7 Block Filling              | 12 Elongation       |
| 3 Binds/Restores Chalky Surfaces | 8 Wind-Driven Rain Resistant | 13 Tensile Strength |
| 4 Water Repellant                | 9 Water Vapor Permeability   |                     |
| 5 Mildew Resistant               | 10 Hairline Crack Bridging   |                     |

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams Representative for additional technical data and instructions.