

PRODUCT GUIDE — TEXTURED

These coatings are used to produce a textured finish on properly prepared masonry surfaces. The aesthetically pleasing result minimizes the effect of defects and irregularities.



	CONFLEX™ FLEXIBLE CONCRETE WATERPROOFER TEXTURED CF15 SERIES	CONFLEX™ ULTRACRETE™ SOLVENT BORNE TEXTURE COATING CF18W0800	CONFLEX™ ULTRACRETE™ SOLVENT BORNE TEXTURE COATING CF18W0810
CHARACTERISTICS	<ul style="list-style-type: none"> Acrylic textured coating for interior/exterior Flat Finish <50 g/L VOC Application temperature 50°-100°F 	<ul style="list-style-type: none"> Styrenated acrylic textured coating for exterior vertical surfaces Finish 0-5 units @ 85° 398 g/L VOC Application temperature >50°F (no reduction); 20°-50°F (5-10% reduction) 	<ul style="list-style-type: none"> Styrenated acrylic textured coating for exterior vertical surfaces Finish 0-5 units @ 85° 398 g/L VOC Application temperature >50°F (no reduction); 20°-50°F (5-10% reduction)
TEXTURE	Textured	Fine	Medium
COLORS	Most	Most	Most
TINTABLE	Yes	Yes	Yes
COVERAGE	125-150 sq. ft.	50-80 sq. ft. (per coat)	50-80 sq. ft. (per coat)
DRY TIME (TO RECOAT)	4 hours	16 hours (77°F), 24-48 hours (20°F)	16 hours (77°F), 24-48 hours (20°F)
SUBSTRATES	Concrete, Stucco	Concrete, Stucco, Split Face Block	Concrete, Stucco, Split Face Block
PRODUCT PROPERTIES	1, 2, 5, 6, 8, 9, 11	1, 2, 6, 8, 9	1, 2, 6, 8, 9

PRODUCT PROPERTY KEY

- | | | |
|----------------------------------|------------------------------|---------------------|
| 1 Alkali Resistant | 6 Self-Priming | 11 Flexibility |
| 2 Efflorescence Resistant | 7 Block Filling | 12 Elongation |
| 3 Binds/Restores Chalky Surfaces | 8 Wind-Driven Rain Resistant | 13 Tensile Strength |
| 4 Water Repellant | 9 Water Vapor Permeability | |
| 5 Mildew Resistant | 10 Hairline Crack Bridging | |

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams Representative for additional technical data and instructions.



CONFLEX™ ULTRACRETE™ SOLVENT BORNE TEXTURE COATING CF18-850 SERIES	CONFLEX™ ULTRACRETE™ ACRYLIC TEXTURE COATING CF17-800 SERIES
<ul style="list-style-type: none"> ■ Styrenated acrylic textured coating for exterior vertical surfaces ■ Finish 0-5 units @ 85° ■ 390 g/L VOC ■ Application temperature >50°F (no reduction); 20°-50°F (5-10% reduction) 	<ul style="list-style-type: none"> ■ Acrylic textured coating for interior/exterior ■ Low Eg-Shel Finish ■ <50 g/L VOC ■ Application temperature >50°F
Smooth	Fine, Medium, Extra Coarse
Most	Many
Yes	Yes
100-160 sq. ft. (per coat)	50-80 sq. ft.
16 hours (77°F), 24-48 hours (20°F)	2 hours
CMU, Concrete, Stucco, Split Face Block	CMU, Concrete, Concrete/Cinder Block, Stucco, Tilt-Up (poured in place), Wood
1, 2, 6, 8, 9	5, 8, 9

PRODUCT PROPERTY KEY

- | | | |
|---|--|---|
| <ul style="list-style-type: none"> 1 Alkali Resistant 2 Efflorescence Resistant 3 Binds/Restores Chalky Surfaces 4 Water Repellant 5 Mildew Resistant | <ul style="list-style-type: none"> 6 Self-Priming 7 Block Filling 8 Wind-Driven Rain Resistant 9 Water Vapor Permeability 10 Hairline Crack Bridging | <ul style="list-style-type: none"> 11 Flexibility 12 Elongation 13 Tensile Strength |
|---|--|---|

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams Representative for additional technical data and instructions.