

PRODUCT GUIDE — TOPCOATS

These versatile topcoats can prolong the lifetime of concrete and masonry by protecting against cracking, weathering and water intrusion while also adding aesthetic appeal.



	CONFLEX™ ACRYLIC COATING CF13 SERIES	CONFLEX™ FLEXIBLE CONCRETE WATERPROOFER SMOOTH CF14 SERIES	LOXON XP™ WATERPROOFING MASONRY COATING	LOXON® SELF-CLEANING ACRYLIC COATING LX13 SERIES
CHARACTERISTICS	<ul style="list-style-type: none"> Acrylic topcoat for exterior Finish 0-10 units @ 85° <50 g/L VOC Application temperature >50°F 	<ul style="list-style-type: none"> Acrylic topcoat for interior/exterior Flat Finish <50 g/L VOC Application temperature 50°-100°F 	<ul style="list-style-type: none"> Styrene acrylic topcoat for exterior Finish 0-10 units @ 85° <50 g/L VOC Application temperature >35°F 	<ul style="list-style-type: none"> Acrylic finish Finish 0-10 units @ 85°F <50 g/L VOC Application temperature >35°F
TEXTURE	Smooth	Smooth	Smooth	Smooth
COLORS	Most	Most	Most	Most
TINTABLE	Yes	Yes	Yes	Yes
COVERAGE	200 sq. ft.	125-150 sq. ft.	90-115 sq. ft.	200-300 sq. ft.
DRY TIME (TO RECOAT)	24 hours	4 hours	24-48 hours (@ 35°-45°F), 24 hours (@ 45°F+)	24 hours
SUBSTRATES	Concrete, Concrete/Cinder Block, Stucco, Split Face Block, Cement Siding	Concrete, Stucco	Concrete, Concrete/Cinder Block, Stucco, Split Face Block, Wood, Cement Siding	Concrete, Concrete/Cinder Block, Stucco, Split Face Block
PRODUCT PROPERTIES	5, 9, 11, 12, 13	1, 2, 5, 6, 9, 11, 12, 13	1, 2, 5, 6, 8, 9, 10, 11, 12, 13	1, 2, 5, 6, 8, 9, 11, 13

PRODUCT PROPERTY KEY

- | | | |
|----------------------------------|------------------------------|---------------------|
| 1 Alkali Resistant | 6 Self-Priming | 11 Flexibility |
| 2 Efflorescence Resistant | 7 Block Filling | 12 Elongation |
| 3 Binds/Restores Chalky Surfaces | 8 Wind-Driven Rain Resistant | 13 Tensile Strength |
| 4 Water Repellant | 9 Water Vapor Permeability | |
| 5 Mildew Resistant | 10 Hairline Crack Bridging | |

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams Representative for additional technical data and instructions.